




100% non-slip surface

Longitudinal white stripes to facilitate the traffic of people with disabilities and guide people with visual impairments



ADVANTAGES



- > Durable
- > 100% recyclable
- > Flexible
- > Retain sand, water & dust
- > Permeable
- > UV, weather & salt water resistance
- > Lightweight
- > Customizable
- > Robust

Technical specificities

Dimension		Roll weight	Roll diameter	Blue Jay	Golden Sand
Width	Length				
1m 3.25ft	5 m 16 ft	8 kg 18lb	30 cm 12"	300248-0500	300252-0500
	10 m 33 ft	15 kg 33 lb	35 cm 14"	300249-1000	300253-1000
	15 m 50 ft	21 kg 46 lb	43 cm 17"	300249-1520	300253-1520
	20 m 65 ft	28 kg 62 lb	50 cm 20"	300250-2000	300254-2000
	25 m 82 ft	34 kg 75 lb	56 cm 22"	300250-2500	300254-2500
	30 m 98 ft	41 kg 90lb	58 cm 23"	300251-3040	300255-3040
1,50m 5ft	5 m 16 ft	11 kg 24 lb	30 cm 12"	300256-0500	300260-0500
	10 m 33 ft	21 kg 46 lb	35 cm 14"	300257-1000	300261-1000
	15 m 50 ft	31kg 68 lb	43 cm 17"	300257-1520	300261-1520
	20 m 65 ft	41 kg 90 lb	50 cm 20"	300258-2000	300262-2000
	25 m 82 ft	50 kg 110 lb	56 cm 22"	300258-2500	300262-2500
	30 m 98 ft	60 kg 132 lb	58 cm 23"	300259-3040	300263-3040
2m 6.5ft	5 m 16 ft	15 kg 33 lb	30 cm 12"	300264-0500	300268-0500
	10 m 33 ft	28 kg 62 lb	35 cm 14"	300265-1000	300269-1000
	15 m 50 ft	41 kg 90 lb	43 cm 17"	300265-1520	300269-1520
	20 m 65 ft	54 kg 119 lb	50 cm 20"	300266-2000	300270-2000
	25 m 82 ft	67 kg 148 lb	56 cm 22"	300266-2500	300270-2500
	30 m 98 ft	80 kg 176 lb	58 cm 23"	300267-3040	300271-3040
3m 10ft	3 m 10 ft	12kg 26 lb	25cm 8"	300470-0306	300276-0306
	5 m 16 ft	22 kg 49 lb	30 cm 12"	300470-0500	300276-0500
	10m 33 ft	42 kg 93 lb	35 cm 14"	300471-1000	300277-1000
	15 m 50 ft	61 kg 134 lb	43 cm 17"	300471-1520	300277-1520
	20 m 82 ft	81 kg 179 lb	50 cm 20"	300472-2000	300278-2000
	25 m 98 ft	100 kg 220 lb	56 cm 22"	300472-2500	300278-2500

Mobi-mat® AFX can support vehicle of 3.5 tons & more (depending on the type of soil)

Tensile strength*	>100 kN/m 10 t/m 680lb/ft
Weight	<2kg/m² 0.4lb/sqft
Temperature of use & storage*	-40°C / + 80°C -104°F / +176°F
Combustion behaviour	UL94 HB

*Non-contractual technical data which does not constitute any guarantee



Up to 5 years warranty



Company certified ISO 9001 and ISO 14001



Mobility: maximum ground grip



Bare foot
> Soft
> Not burn feet



ADA Compliance
Disable standards



Pedestrians and family with
> Strollers
> Luggage



Traffic
> Bikes
> Quads, Scooters...
> Cleaning and service vehicles



Light strip option - USB power cable
Maximum power 5W

Quick installation & low maintenance

QUICK INSTALLATION

Mobi-mat® is easy and quick to install.
Unpack, unroll and anchor the mat on the ground !

Additional anchoring options :

- **Concrete anchoring kit**
- **Wood anchoring kit**
- **Compact ground anchoring kit**
- **Underwater anchoring kit for soft ground**
- **Underwater anchoring kit for compact ground**

EASY MAINTENANCE

Excellent corrosion resistance:

- **Galvanized steel anchors**
- **Aluminum rivets and stainless steel eyelets**

Use a broom, a leaf blower or a high pressure water jet to clean Mobi-mat®.



*All anchors are provided with the mat.
 Depending on your mats' dimensions, the number of eyelets and anchors will be different*

Multiple applications



BEACHES &
BOATRAMPs



PARKS &
GARDENS



TOURISM



CONSTRUCTION &
LANDSCAPING



EVENTS



HOUSES &
POOLS



SKI STATIONS



FARMING



What are our complementary products?

Mobi-roller™
Mat dispenser



Mobi-chair™
Floating Wheelchair



Mobi-com™
Advertising mat



Mobi-fence™
Sand fence



 info@mobi-mat.com