



Control of sand,
dust or snow
movements

Contribution to
the dune
reconstruction



ADVANTAGES



> UV, sea water, wind resistance

> 100% recyclable

> Easy installation & maintenance

> Flexible

> Lightweight

> Robust

> Retains dust,
sand or snow

Technical specificities

Height	1 m 3.25 ft	2m 6.5 ft
Length	50 m 164 ft	50m 164 ft
Pockets diameter	10 cm 4"	15 cm 6"
Weight	20 kg 44 lb	35 kg 77 lb
Color	Beige	Beige
Reference	300460-5000	300463-5000



Mobi-fence™ withstands winds over 180km/h

Weight	340 g/m ² 0.07 lb/sqft
Temperature of use and storage*	-40°C / + 80°C -104°F / +176°F

*Non-contractual technical data which does not constitute any guarantee



Up to 5 years
warranty



Company certified
ISO 9001 and ISO 14001



Innovative, ecologic & durable



- > Low mesh opening
- > High permeability
- > Pockets directly included in the fabric



- > Preservation of flora & fauna



- > Thick fabric
- > Strengthened edges

Quick installation & low maintenance

QUICK INSTALLATION

The setting of a Mobi-Fence™ is easy and quick thanks to its lightness, its flexibility and the pockets included in the fabric to slide the stakes.

The installation comes down to driving the stakes.



LOW MAINTENANCE

Mobi-fence™ does not require any special maintenance and fits perfectly and easily into any type of landscape.



Before
Mobi-fence
installation



After
+10 years after
Mobi-fence
installation

Mobi-fence™ provides sandbank or dust control, dune reinforcement and sea erosion control.

Mobi-fence™ protects against strong rising tides, stabilized the base of the dune, and protects against sand being carried away by the tide or wind.

Pathways, roads, parking lots, recreation areas and buildings are protected and the development of flora and fauna are encouraged.

Multiple applications

ACCESS & INFRASTRUCTURE PROTECTION



DUNE REINFORCEMENT



What are our complementary products?

Mobi-mat® Accessibility mat



Mobi-chair™ Floating Beach Wheelchair



Mobi-com™ Advertising mat



Mobi-deck™ Rigid panel



 info@mobi-mat.com