



2 widths available  
Removable loading axle

Aluminium structure &  
anticorrosion treatment

UV & salt water  
resistance



## Technical specifications

Dimension		Weight	Reference
Mat width (m   ft)	Max length (m   ft)		
1,5 m   5ft	<b>AFX type</b> 50,4m   166ft <b>A2X type</b> 40,4m   133ft	23 kg   51 lb	220 464
2m   6.5ft	<b>AFX type</b> 30,4m   100ft <b>A2X type</b> 30,4m   100ft	27 kg   60 lb	220 463
Vehicle towing bar (option)			216 836
Extra axle 1,5 m   5ft (option)			216 842
Extra axle 2m   6.5ft (option)			216 844

Exact widths in meter are → 1,53m | 1,98m

Build quickly and safely Mobi-mat® temporary roads.

Mobi-roller™ is designed to transport, deploy and stock one or more Mobi-mat® until 50 meters - manually or with a vehicle in a few minutes.

EASY  
ASSEMBLY



ROBUST SYSTEM



EASY TRANSPORT  
& STORAGE



Mobi-roller™ is delivered in kit ready to be assembled in few minutes.  
Deployment can be done in **forward or reverse gears** thanks to the reversible fixing system.  
It has to be stored in a clean and dry place.

 [info@mobi-mat.com](mailto:info@mobi-mat.com)